

MAYURA BUMI ENGINEERING SDN BHD (8023393-T)

Tb 7-1A, Suite 2, The Landmark, Jalan Batu Nilam 16, Bandar Bukit Tinggi 2, 41200 Klang. Selangor, Malaysia. Tel: 03-3319 1889 ext 102 Fax: 03-33223601 Email: <u>bumicoat@bumi.mayuraengineering.com.my</u>

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

BUMI COAT Product name

Colour Grey

Product Type Solvent based composition - Flammable

TB 7-1A, Suite 2, The Landmark, Jalan Batu Nilam 16, Bandar Company Address

Bukit Tinggi 2, 41200 Klang, Selangor, Malaysia.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	%	Exposure Limits
Xylene	1330-20-7	10-20	not established
Butanol -n	71-36-3	10-20	not established
Modified Aluminium silicate		20-40	not established
Modified Magnesium silicate		10-20	not established
Additive (Proprietary)		5-10	not established

3. HAZARDS IDENTIFICATION

Emergency Overview: Flammable liquid. Causes moderate eye, skin, and digestive tract

irritation. Spray mist causes irritation to respiratory tract. Release into surface water is harmful to aquatic life. Combustible. Spills are slippery. Reacts with acids, ammonium salts, reactive metals and

some organics.

: Causes moderate irritation to the Eye contact

eyes. Skin contact : Causes moderate irritation to the skin. Inhalation : Spray mist irritating to respiratory

system.

Ingestion : May cause irritation to mouth, esophagus, and stomach. Chronic hazards : No known chronic hazards. Not listed as a

carcinogen.

4. FIRST AID MEASURES

Eye : In case of contact, immediately flush eyes with plenty of water. Get

medical attention.

Skin : In case of contact flush skin with plenty of water. Remove

contaminated clothing and shoes. Inhalation: Remove to fresh air.

Get medical attention.

: If swallowed, DO NOT induce vomiting. Get medical attention Ingestion

immediately.

5. FIRE FIGHTING MEASURES

THE PRODUCT IS FLAMMABLE

Suitable extinguishing media – Foam, Carbon dioxide

Sunday, May 01, 2021

MAYURA BUM

MAYURA BUMI ENGINEERING SDN BHD (8023393-T)

Tb 7-1A, Suite 2, The Landmark, Jalan Batu Nilam 16, Bandar Bukit Tinggi 2, 41200 Klang, Selangor, Malaysia. Tel: 03-3319 1889 ext 102 Fax: 03-33223601

Email: bumicoat@bumi.mayuraengineering.com.my

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with skin and eyes, Spillages can cause slippery situations

Collect as much as possible in a (clean) container or by absorbent material

7. HANDLING AND STORAGE

Handling : Avoid contact with the concentrated product. The product is

sticky. Use protective gloves and mask.

Storage : Keep packaging / storage vessel closed. Protect from freezing. Keep

away from sources of ignition

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measures / system design : NA

Respiratory protection : prevent breathing of the spray Hand protection : wear chemical resistant gloves

Eye protection : wear suitable goggles

Skin protection : wear suitable protective clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Thick liquid

Color : Grey

Odor : xylene, butanol.

PH : na

Specific gravity : 1.6 - 1.7

g/cc Solubility in water: not Miscible. Flash point: 13 C

10. STABILITY AND REACTIVITY

Stability : This material is stable under all conditions of

use and storage.

Conditions to avoid : fire, ignition sources
Materials to avoid : water, oxidizing
agent Hazardous decomposition products : carbon dioxide

11. TOXICOLOGICAL INFORMATION

When tested for eye and skin irritation potential, a similar material caused moderate irritation to the eyes and moderate irritation to the skin. The acute oral toxicity of this product has not been tested.

12. ECOLOGICAL INFORMATION

This material is toxic to aquatic systems in high concentrations.

Sunday, May 01, 2021

MAYURA BUM

MAYURA BUMI ENGINEERING SDN BHD (8023393-T)

Tb 7-1A, Suite 2, The Landmark, Jalan Batu Nilam 16, Bandar Bukit Tinggi 2, 41200 Klang, Selangor, Malaysia. Tel: 03-3319 1889 ext 102 Fax: 03-33223601 Email: bumicoat@bumi.mayuraengineering.com.my

13. DISPOSAL CONSIDERATIONS

Do not dump in sewers, on the ground, into water bodies Recommended Method of Disposal: Dispose according to central and local governmental regulations.

14. TRANSPORTATION INFORMATION

Flammable liquid

15 REGULATORY INFORMATION

Hazard Symbols : Flammable

liquid R-phrases : None S-phrases : None

16. OTHER INFORMATIONS

The product is meant for industrial use

THE INFORMATION ON THIS SAFETY DATA SHEET IS BELIEVED TO BE ACCURATE. THIS DOCUMENT IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONS FOR HANDLING A CHEMICAL BY A PERSON TRAINED IN CHEMICAL HANDLING. MAYURA BUMI ENGINEERING SDN BHD MAKES NO WARRANTY WITH RESPECT TO SUCH INFORMATION OR THE PRODUCT TO WHICH IT RELATES, AND WE ASSUME NO LIABILITY RESULTING FROM THE USE OR HANDLING OF THE PRODUCT TO WHICH THIS SAFETY DATA SHEET RELATES. USERS AND HANDLERS OF THIS PRODUCT SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION PROVIDED HEREIN FOR THEIR OWN PURPOSES.